

(12) United States Patent Hughes

(54) APPARATUS FOR MARKING A LABORATORY SAMPLE CARRIER

(71) Applicants: PYRAMID INNOVATION.

Netherfield, Sussex (GB); Thomas Fergus Hughes, Netherfield, Sussex

(72) Inventor: Thomas Fergus Hughes, Netherfield

Assignee: **PYRAMID INNOVATION (partial** (73)

interest), Netherfield (GB)

Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

(21) Appl. No.: 14/907,784

PCT Filed: Aug. 5, 2014

(86) PCT No.: PCT/GB2014/052393

§ 371 (c)(1),

Jan. 26, 2016 (2) Date:

(87) PCT Pub. No.: WO2015/019072

PCT Pub. Date: Feb. 12, 2015

(65)**Prior Publication Data**

> US 2016/0185132 A1 Jun. 30, 2016

(30)Foreign Application Priority Data

(51) **Int. Cl.**

(2006.01)B41J 2/15 B41J 11/00 (2006.01)B41J 3/407 (2006.01)

(52) U.S. Cl.

B41J 11/0045 (2013.01); B41J 3/407 CPC (2013.01); **B41J** 3/4073 (2013.01)

(10) Patent No.:

(45) **Date of Patent:** May 2, 2017

(58) Field of Classification Search

CPC B41J 2/2142; B41J 2/0451; B41J 2/16579;

B41J 2/01; B41J 2/2139;

US 9,636,929 B2

(Continued)

(56)References Cited

U.S. PATENT DOCUMENTS

4/1999 Matsumoto et al. 5,893,263 A 2002/0167577 A1 11/2002 Kiene

2003/0059281 A1 3/2003 Kiene et al.

FOREIGN PATENT DOCUMENTS

2 235 163 A 2/1991 GB WO 2007/135396 A1 WO 11/2007

OTHER PUBLICATIONS

PCT/GB2014/052393 International Search Report and Written

Opinion.

GB 1314104.9 Search Report under Section 17.

Primary Examiner — Lamson Nguyen

(74) Attorney, Agent, or Firm — Fay Sharpe LLP

ABSTRACT

An apparatus (1) for marking a laboratory sample carrier (2), includes a guide (5) configured to guide a sample carrier (2) from an entry location (6) to an exit location (7), and a print head (23) configured and positioned to mark a sample carrier (2) at a marking location (24) at a guide position intermediate the entry and exit locations (6, 7). The guide (5) is inclined such that a laboratory sample carrier (2) can travel from the entry to the exit locations (6, 7) under the influence of gravity. The apparatus (1) further includes a selectively deployable stop (41) for arresting the travel of a sample carrier (2) down the guide (5) at the marking location (24), the stop (41) being undeployable to allow the sample carrier (2) to travel from the marking location (24) to the exit location (7).

20 Claims, 12 Drawing Sheets

